Manufactured Home

Rating Guide

| ITEM | Crystal Mountain Homes |
|---------------------------|---------------------------|
| Floor Decking | VERY GOOD |
| Floor Insulation R-rating | EXCELLENT |
| Deck fastened by | SUPERIOR |
| Floor Joists | EXCELLENT |
| Carpet | AVERAGE |
| Fastened to floor | EXCELLENT |
| Vinyl covereing | VERY GOOD |

Floors, floor covering

| s | Front door | EXCELLENT |
|-----------------|------------------------|-----------|
| | Rear door (to outside) | EXCELLENT |
| ð | Matching key locks | EXCELLENT |
| Doors & windows | Interior doors | SUPERIOR |
| ors 8 | Interior door hinges | EXCELLENT |
| å | Windows | EXCELLENT |
| | | |
| 20 | Water piping | SUPERIOR |
| bing | Pipe fittings | EXCELLENT |
| | | |

EXCELLENT

| Mainstream site-built homes & some high-end manufactured homes | | Manufactured Home mid- to high | | Manufac- tured Home low- to mid | Manufactured Home entry- to low | | me | |
|---|-------------------------------|-----------------------------------|------------------------------|---------------------------------------|------------------------------------|--------------------------------|-----------------------------|-----------|
| Excellent | Superior | Very Good | Good | Above average | Average | Below average | Poor | Very Poor |
| 1-1/8" Plywood | 3/4" Plywood or OSB | 5/8" Pywood | 3/4" Cresdek or Novadek | | 5/8" Cresdek or Novadek | 3/4" generic particle board | 5/8" generic particle board | |
| | R-33 | R-21 | | | R-11 R-7 | | R-7 | |
| | Glued & Screwed Glued & Naile | | | d | Glued & Stapled | | | |
| 2"x8" 16" O.C. (2"x6" ok for singles) | | | 2"x6" 16" O.C. | 2"x6" greater than 16" O.C. | | | | |
| 32-5 | 32-50 oz. 26-31 oz. 22-25 oz. | | 22-25 oz. | 19-21 oz. | 16-18 oz. | 15 oz. | or less | |
| Install over cushion with tackless strip using power stretcher or kee kicker | | | Tackless strip or staples | Stapled only Stapled, glued | | l, glued | | |
| High quality tiles or rolled vinylHeavy, quality rolled linoleum with now/urethane wear layerseams, urethane wear layer | | | Middle grade lino | Economy grade vinyl linp | | linp | | |

| 36"x8 | D" 6-panel steel front door w/ dead bolt lock and pe | • • | 36"x80" steel | Aluminum 34" or 35" x 74", 76" or 78" | |
|---|---|------------|-------------------------------|---|--|
| 36"x80" steel, dead bolt, dual glaze window (doors to attached garage are 32" wide) 36"x80", dead bolt | | | Steel 32"x74" x76"x78" | Aluminum 32"x74" or 76" or 78" | |
| | Yes | | | No | |
| 30"x80" solid wood 6-panel | 30"x80"wood frame, hollow core | | | 26"x74" plain luan, hollow core | |
| 3 | 3, full mortised: both door | and casing | 2, mortised to door or casing | 2, surface mount | |
| White vinyl vacuum sealed dual glazed w/ Low-E | | | White vinyl dual glazed | Single pane, aluminum frame, w/ self storing storm windows | |

| 8 | Water piping | |
|---------|-----------------------|--|
| bir | Pipe fittings | |
| lumbing | Water Shut-off valves | |
| ≧∟ | Outside Faucets | |

| Copper | | Pex or CPVC | | | |
|--------------|-----|-----------------|--|--------------------------|--|
| Copper/brass | | Brass | | Plastic | |
| | | At all fixtures | | Main water shut-off only | |
| | 2 1 | | | None | |